

**ELIKA**<sup>™</sup>  
ACCESS SYSTEMS

The only cellular and VoIP telephone entry system with **PTCRB, FCC, and mobile network certifications.**



## ELIKA 460 Telephone Entry System

FOUR COLOR OPTIONS TO CHOOSE FROM




SILVER  
(STANDARD)



GUNMETAL



BRONZE



WHITE

## ELIKA EXCLUSIVE FEATURES

### WEB BASED APP

- Allows remote programming of the system and updates in real-time
- Compatible with Windows, MacOS, Linux, Chrome OS, iOS and Android operating systems

### MULTIPLE WIRELESS COMMUNICATION OPTIONS

- Choose between a variety of options: 3G, 4G, and VoIP (Voice Over Internet Protocol) over Ethernet or Wireless

### DAY / NIGHT DIGITAL CAMERA

- Digital camera captures an image of every event and stores it in its event log with a time stamp

### FULLY CERTIFIED

- The Only Cellular and VoIP Telephone Entry System that is PTCRB, FCC, and Mobile Network Certified in the United States

### ELIKA SMART CALL

- This feature allows up to 3 contact phone numbers per user

### SOLAR READY

- Can be powered with standard 12 volt solar panel and battery

### BUILT IN SURGE AND LIGHTNING STRIKE PROTECTION

- Protection up to 200 Million Watts

### HARDWARE SETTINGS REMOTE ADJUSTMENT

- Sound and light settings adjustable remotely.

### DIGITAL NOISE AND ECHO CANCELLATION

- Eliminates the need for feedback adjustment
- Ensure clear voice communication

## OPTIONAL SERVICES

### BATTERY BACKUP

- In the event of power loss, your telephone entry system will remain functional

## DESIGN

### FOUR COLOR OPTIONS

- Silver, White, Gunmetal, Bronze

### BACKLIT KEYPAD

- Fully adjustable brightness level

### COURTESY LIGHT

- Adds security and convenience under low light conditions

### ILLUMINATED CALL BUTTON

- Clearly visible at night time

### 4 LINE LCD DISPLAY

- Allows the display to list up to 4 tenants at one time

## ENCLOSURE COMPONENTS

### STAINLESS STEEL KEYPAD

- Provides a longer lasting, more durable surface

### DIGITAL MICROPHONE

- Ensures clear voice communication

## PROTECTION

### ELECTRICAL PROTECTION

- Short Circuit, Electrostatic Discharge, Reverse Polarity and Relay Contact protection

### ALUMINUM ENCLOSURE

- UV powder coated provides additional protection against corrosion and weather elements

### IP65 RATED ENCLOSURE

## STANDARD FEATURES

### WIEGAND READER INTERFACE

- Available port for Wiegand communication
- Standard 26 bit Wiegand input port

### TIMERS

- Seven programmable timers, each with seven days of the week

### INDIVIDUAL TIME ZONES

- For each code, Elika Smart Key, shared key and RFID/HID
- Individual call time schedule per phone number

### HISTORY LOG REPORTS

- Track usage history through report logs

### INTERNAL MEMORY

- Up to 200,000 total unique users/codes

- 100,000 history events

### PROGRAMMABLE ACCESS CODES

- 3 to 6 digit code that can be used to strike one or both relays
- Not bound by set length. Each user can select any code from 3 to 6 digits long

### TWO RELAY OUTPUT WITH PROGRAMMABLE STRIKE TIME

### TWO PROGRAMMABLE CONTACT INPUTS

### IMPORT DATABASE FROM EXCEL (CSV)

- Makes importing existing databases a breeze

## SECURITY AND SAFETY

### TAMPERING AND ACCESS

- Vandalism proof casing
- Security screws

### FORCED ENTRY SENSOR WITH INTERNAL SIREN AND FAIL SECURE OUTPUT

- A numerical passcode is required before opening its enclosure

### REAL-TIME DIAGNOSTICS

- Get real-time diagnostic information
- Remote automatic software updates

## SPECIFICATIONS

### WARRANTY

- 2 Year limited warranty

### OPERATIONAL VOLTAGES

- 12V-16V AC/DC
- 12 Watts
- Solar Compatible

### RELAY CONTACT

- 5 Amps

### DIMENSIONS

- Height 8.5" x Width 12" x Depth 4.25"

### OPERATING TEMPERATURE

- -40F to +167F